



Two-bolt flanged housing units

Oval version
With adapter sleeve



UKFL



UKFL

Dimension table · Dimensions in mm

Designation	Mass m ≈kg	Dimensions										Housing	Radial insert ball bearing	
		d	H	J	L	A	A ₁	A ₂	N	B ₁	d ₃ max.			
UKFL205	0,69	20	130	99	68	27	15	16	16	16	35	38	FL205	UK205
UKFL206	0,94	25	148	117	80	31	14	18	16	16	38	45	FL206	UK206
UKFL207	1,29	30	161	130	90	34	16	19	16	16	43	52	FL207	UK207
UKFL208	1,56	35	175	144	100	36	16	21	16	16	46	58	FL208	UK208
UKFL209	2,08	40	188	148	108	38	18	22	19	19	50	65	FL209	UK209
UKFL210	2,4	45	197	157	115	40	18	22	19	19	55	70	FL210	UK210
UKFL211	3,04	50	224	184	130	43	20	25	19	19	59	75	FL211	UK211
UKFL212	4,05	55	250	202	140	48	20	29	23	23	62	80	FL212	UK212
UKFL213	4,84	60	258	210	155	50	24	30	23	23	65	85	FL213	UK213
UKFL215	6,17	65	275	225	165	56	24	34	23	23	73	98	FL215	UK215
UKFL216	7,74	70	290	233	180	58	24	34	25	25	78	105	FL216	UK216
UKFL217	9,08	75	305	248	190	63	26	36	25	25	82	110	FL217	UK217
UKFL218	10,9	80	320	265	205	68	26	40	25	25	86	120	FL218	UK218